



ON-TRACK PLANT

ENGINEERING CONFORMANCE CERTIFICATE

This certificate is issued in accordance with RIS-1530-PLT Issue 6.

NAME OF CERTIFICATION BODY	ACCREDITATION CODE
AEGIS Certification Services Ltd	AC

Machine Class/Description	010/Rexquote/T16/HAS/0A
Machine Owner	L&W Contractors Ltd
Issue Date	24 th March 2022
Expiry Date	21 st March 2029

Machine Number: **99709 010865-2**

First of Class	No
Certificate Number of First of Class	21/0694/19

Authorised by:



Sam Barrett
AEGIS PAB Signatory

Official Stamp



Reason for Issue and Scope of Work

Previous Certificate:

Certification of new Rexquote T16 Rail Trailer.
Rexquote Serial No. 2349.

Assessed for compliance with RIS-1530-PLT, Issue 5.

Expiry date conforms the requirements of RIS-1530-PLT, Issue 5.

Network Rail Asset Info. Copy

Certificate Number: AC/0112/22

This certificate:
Upgrade to RIS-1530-PLT Issue 6.

Deviations Associated with this Certificate

Tracker Number None
Description None

Previous Certificate Number: IF/0192/15

Approved User Documentation

ID No.	Title	Issue No.	Date
RQM60109V6	Rexquote T16 Trailer Pneumatic/Hydraulic Braking, Rail Mounted Trailer Operating and Maintenance Manual	1	6th September 2019

Limitations of Use

1. The trailer shall only operate inside possessions.
2. In travelling and working modes, the trailer is within Plant gauge, as defined by RIS-1530-PLT.
3. The trailer shall not on/off track or work on live conductor rail lines.
4. The trailer may on/off track, travel and work under live OLE in conjunction with a safe system of work as determined and authorised by taking guidance from the requirements of GE/RT8024.
5. The trailer may not activate train operated points.
6. The trailer shall not travel or work on track with:
> cants greater than 200mm; gradients greater than 1 :25; and/or curves less than 80m.
7. The trailer cannot be on/off tracked in the laden condition.
8. For on/off tracking, a site specific plan shall be used taking account of the requirements of the applicable Module in Network Rail Infrastructure Plant Manual NR/L2/RMVP/0200.
9. In travelling and working mode the trailer shall be the subject to limitations of the towing vehicle.
10. The trailer payload of 20tonnes shall not be exceeded.

Supplementary Information

1. Rexquote 4-wheel trailer with 5m bed to work with compatible RRV.
2. Rexquote Serial No. 2349. L&W Fleet No. RRT 28.
3. Fitted with air/hydraulic spring-operated emergency/parking brake and air/hydraulic operated service brake.
4. - Air parking brake release pressure 5 bar; service brake pressure 0-10 bar.
- Hydraulic parking brake release pressure 25bar; service brake pressure 0-90bar.



- 5. Gross weight: 22.75tonnes.
- 6. Trailer payload: 20tonnes.
- 7. Tare weight: 2.75tonnes.
- 8. Maximum speeds (travel and working) not to exceed:
 - > 10mph plain line;
 - > 5mph switches and crossings;
 - > 5mph raised check/guard rails

Serial Number	2349
Fleet Number	RRT 28

Authorised by:

Sam Barrett
AEGIS PAB Signatory
