



On-Track Plant Engineering Conformance Certificate

This certificate is issued in accordance with RIS-1530-PLT Issue 6

NAME OF VEHICLE ACCEPTANCE BODY

SNC-Lavalin Rail & Transit Verification Limited

ACCREDITATION CODE

21

Vehicle Class / Description

010/Rexquote/T4/0A

Vehicle Owner

L&W Contractors Ltd

Issue Date

17 May, 2017

Expiry Date

17 May, 2024

Vehicle Number(s)

99709_010333-1

First Of Class

99709 010334-9 on Engineering Conformance Certificate 21/0365/17 against RIS-1530-PLT issue 6.

Authorised by:

Adrian Staples

SNC-Lavalin Rail & Transit Verification Limited

Adrian Staples

OFFICIAL STAMP



SNC · LAVALIN

Reason for issue and Scope of Work

Certification of upgraded T4 rail trailer, including modification to air park/service braking.

Rexquote No. 1631. L&W Contractors Fleet No. RRT20.

Assessed for compliance with RIS-1530-PLT, Issue 6.

Expiry date conforms the requirements of RIS-1530-PLT.

Deviations associated with this certificate

None

Previous Certificate Number

No previous Engineering Conformance Certificate against RIS-1530-PLT Issue 6.

Previous Engineering Acceptance Certificate: NS/5015/09.

Customer Copy

Certificate Number: 21/0462/17



On-Track Plant

Maintenance Plan Details

Rexquote Trailer Operating and Maintenance Manual RQM60062v07; Issue 1; Dated 28 Mar 2017.

Limitations of Use

1. The trailer shall only operate inside possessions.
2. In travelling and working modes, the trailer is within Plant gauge, as defined in RIS-1530-PLT. It exceeds the Plant Gauge as defined in RIS-1530-PLT, in the lower sector limit above rail level and between the rail wheels. The brake discs protrude by 34mm below the 114mm limit.
3. The trailer shall NOT on/off track or work on live conductor rail lines.
4. The trailer may on/off track, travel and work under live OLE in conjunction with a safe system of work (SSoW), as determined and authorised by taking guidance from the requirements of GE/RT8024.
5. The trailer will NOT activate train operated points.
6. The trailer shall NOT travel or work on track with:
 - > cants greater than 200mm; gradients greater than 1:25; and/or curves less than 80m.
7. The trailer cannot be on/off tracked in laden condition.
8. For on/off tracking, a site specific plan shall be used taking account of the requirements of the applicable Module in Network Rail Infrastructure Plant Manual NR/Plant/0200.
9. In travelling and working mode the trailer shall be the subject to limitations of the towing vehicle.
10. The trailer payload of 21tonnes, evenly distributed, shall NOT be exceeded.

Supplementary Information

1. Rexquote 4-wheel trailer with 5.02m bed to work with compatible RRV.
2. Rexquote Serial No. 1631; L&W Contractors Fleet No. RRT20.
3. Fitted with air spring-operated emergency/parking brake and air operated service brake.
4. Air parking brake release pressure 5-10 bar; service brake pressure 0-10 bar.
5. Gross weight: 24tonnes.
6. Trailer payload: 21tonnes.
7. Tare weight: 3tonnes.
8. Maximum speeds (travel and working) not to exceed:
 - > 10mph plain line;
 - > 5mph switches and crossings;
 - > 1mph raised check/guard rails.
9. When fitted with a Rexquote Personnel Transporter PT1.
 - The twist locks shall be engaged and the earth bonds secured.
 - The controls to the towing vehicle shall be connected and verified as correct and operational before use.
 - The PT1 shall only be occupied and used in accordance with the SSoW for the possession.